




CNC Horizontal Turning Center

SC 6000 Series


UNION MT
Your Choice Of Partner



Difference begins from material



and for the markets. Oil, Energy, Construction, Hydraulic, Pneumatic Equipment, Industry Machinery and etc.

Spindle Output



Main Features

- Air chuck and manual chuck installed on both spindle ends provide long work-pieces machining capability.
- 3-step gear headstock provide extra torque 9564 Nm for heavy duty cutting and operation efficiency.
- One body slant 45 degrees cast iron base use Meehanite casing iron, alloy ingredients, tempered and aged process for stress relief to assure stability and longevity
- Strategically-ribbed, rigid machine structure and wider box ways for assuring rigidity and longevity life.
- Hand scraped skill assure 16 dots per inch and sustain trapped film of oil between box guide ways and saddle for smooth travelling.



CAPACITY	SC 6011	SC 6017	SC 6022	SC 6032
Max. swing diameter		970 mm (38.19")		
Swing over saddle		720 mm (28.35")		
Max. turning diameter		850 mm (33.46")		
Max. turning length	1110 mm (43.70")	1700 mm (66.93")	2200 mm (86.61")	3200 mm (125.98")
Chuck size		18" (Optional 20" / 21" / 24" / 32")		
SPINDLE				
Spindle nose		A2-11 (Optional A2-15 / A2-20)		
Hole through spindle		A2-11 160 (6.30") / A2-15 230 (9.06") / A2-20 305 (12.01") 360 (14.17")		
Spindle motor peak power		37 kW (50 HP)		
Spindle peak torque		9564 Nm @37 rpm S3 25%		
X & Z AXIS				
X axis travel		450 mm (17.72")		
Z axis travel	1250 mm (49.21")	1750 mm (68.90")	2250 mm (88.58")	3250 mm (127.95")
X axis rapids		12 m/min. (472 ipm)		
Z axis rapids		16 m/min. (630 ipm)		
X axis servo motor		X axis 4 kW (5.4HP)		
Z axis servo motor		Z axis 7 kW (9.3HP)		
Slide way type		Box Way		
TURRET				
Turret type		Servo drive 12 stations		
Square tool shank size		32 mm (1-1/4")		
Boring tool shank size		50 mm (1.97")		
TAILSTOCK				
Quill center taper		MT #6		
Quill diameter / travel		200 mm (7.87") / 200 mm (7.87")		
Tailstock base travel	850 mm (33.46")	1450 mm (57.09")	1950 mm (76.77")	2950 mm (116.14")